

HT9980A series PV Safety Tester



● OVERVIEW

HT9981A is a three-in-one comprehensive tester developed by our company for the photovoltaic industry automation test equipment. Standard data acquisition software, support U disk remote upgrade program. Comply with photovoltaic standards IEC61215, IEC61730.

● FEATURES

- 3-in-1 comprehensive test, testing withstand voltage, insulation resistance and grounding resistance
- Equipped with PLC and communication interface, able to external connected to supporting facilities to achieve automated testing
- With upper and lower limits setting, using sound and light alarm to eliminate product missed detection
- Full keyboard operation, simple and easy to read and operate, more convenient to set the parameters
- Four-wire test perfectly eliminates wire resistance, and the calculation is more accurate

● APPLICATION

HT9980A and HT9981A as PV safety testers used for photovoltaic module safety parameters, it is also be used for household appliances, electronic instruments, electronic equipment, electronic components, wires and cables and other electrical products withstand voltage, insulation test and ground test.

● SPECIFICATION

Model	HT9980A	HT9981A
DC withstand voltage measurement		
Voltage range	0~8000V	0~10000V
Voltage output resolution	0.001kV	

Voltage output accuracy	$\pm(3\%+5 \text{ counts})$	
Current measurement	0~5mA	
Current resolution	0.01 μ A	
Current accuracy	$\pm (2\%+ 2 \text{ counts})$	
Insulation resistance test		
Voltage range	0~2000V	0~3000V
Voltage resolution	0.001kV	
Voltage accuracy	$\pm (3\%+ 5 \text{ counts})$	
Resistance range	0.1M Ω ~50G Ω	0.1M Ω ~99G Ω
Resistance accuracy	$\pm(2\% \text{ display value} + 3 \text{ counts})$ (100k Ω -999M Ω) ; $\pm(5\% \text{ display value} + 3 \text{ counts})$ (1.00G Ω -9.99G Ω ; $\pm(20\% \text{ display value} + 3 \text{ counts})$ (10G Ω -50G Ω))	$\pm(2\% \text{ display value} + 3 \text{ counts})$ (100k Ω -999M Ω) ; $\pm(5\% \text{ display value} + 3 \text{ counts})$ (1.00G Ω -9.99G Ω) ; $\pm(20\% \text{ display value} + 3 \text{ counts})$ (10G Ω -99G Ω)
Ground resistance test		
Current range	10A~60A	10A~80A
Current resolution	0.01A	
Current accuracy	$\pm (2\%+5 \text{ counts})$	
Resistance range	0~600.00m Ω (10.00A~20.00A); 0~300.00m Ω (20.01A~30.00A); 0~200.00m Ω (30.01A~40.00A); 0~150.00m Ω (40.01A~50.00A); 0~120.00m Ω (50.01A~60.00A);	0~600.00m Ω (10.00A~20.00A); 0~300.00m Ω (20.01A~30.00A); 0~200.00m Ω (30.01A~40.00A); 0~150.00m Ω (40.01A~50.00A); 0~120.00m Ω (50.01A~60.00A); 0~100.00m Ω (60.01A~70.00A) 0~80.00m Ω (70.01A~80.00A)
Resistance resolution	0.001m Ω	
Resistance accuracy	$\pm (2\%+3 \text{ counts})$	
Size	427mm*406mm*87mm	
Accessories	HT9933, HT9950, HT9900, JK381-10P-T, HT9800, power cord	

ISOTEST, S.L.,

Dirección fiscal: C/Ikea, 51—48940—Leioa—Bizkaia

Dirección almacenes y Laboratorios: C/Brazomar 52A, nº 7—39700—Castro-Urdiales—Cantabria

 Tfno.: 944803040—Fax: 944348191—email: isotest@isotest.es— web: <https://isotest.net>